

IMT SiteStar

IMT SiteStar (open) body to include one color Linen White (N0006) Imron paint, access ladder, recessed taillights, (3) above deck compartments on the street side, (1) above deck compartment on the curb side, filter drain box in rear service compartment, hose reel shelf, grommet mounted backup alarm, (6) 12V halogen work lights with switches, installation kit, gripstrut in walkway, and rear dropped compartment with fluid containment tank/bumper and rollup aluminum door.

- **Truck Chassis**

- Sterling LT9500
- Cat C11 Engine
- Fuller RTO 14908LL Transmission
- 20,000lb Front Axle
- 40,000lb Rear Axle
- 60,000lb GVW



- **MAIN BODY PLATFORM**

- 13' 3" SiteStar Body

- **SAFETY EQUIPMENT**

- ICC Safety kit (Required for drive away units)
- 20-pound fire extinguisher w/bracket

- **"MAIN HYDRAULIC SYSTEM**

- You must pick an engine speed control for this system."
- PTO with Air Shift (Can not be used on automatic transmissions)

- **"HYDRAULIC PUMPING SYSTEM**

- (Maximum 2 pumping systems per unit)"
- 4 Section hydraulic pumping system

- **"DIESEL SYSTEM**

- System includes tank w/ROPS, emergency shut-off and installation kit."
- 2,000 gallon steel tank (oval) 9 ft. long X 96"W
- Emergency shut off valve
- **DIESEL FUEL PUMPS**
- Pump assy - hydraulic driven 0-33 gpm w/installation kit

- **WATER / ANTI-FREEZE SYSTEM AIR PUMP**

- Water/Anti-freeze System: Air pump assembly (M-2)



- **DIESEL FUEL METERS**

- 1.5" Flow master fuel meter 0-50 GPM

- **DIESEL FUEL REEL**

- Spring rewind reel Hannay 1" X 50' w/hose and ballstop

- **DIESEL FUEL NOZZLES**

- Automatic 1" (Diesel) w/swivel
- ZZ9A Wiggins

- **OIL SYSTEM TANKS**

- 75 gallon polyethylene tank

- **OIL REELS**

- 1/2" x 50' hose reel, includes hoses and ballstop

- **OIL NOZZLES (Required Selection)**

- Non-metered valve high flow, cap & chain (oil)
- Nozzle with holder (preset metered valve 0-60 quart (oil) rigid end)

- **"SALVAGE SYSTEM TANKS**

- (Air operated)"
- 190 gallon polyethylene tank

- **SALVAGE REELS**

- 1.25 X 35ft Salvage Reel

- **SALVAGE SYSTEM AIR PUMP**

- Salvage Systems: Air pump assembly (M-4) Wilden (min. 20 CFM required)



- **"GREASE SYSTEM"**
- **(Air operated)"**
- 120# Grease System
- **AIR SYSTEM
OPTIONS**
- DA435HA 35CFM @ 100 PSI
- Hannay 1/2" X 50' hose reel w/hose and ball stop
- 1/2" moisture separator/regulator/oiler
- **"WATER / ANTI-FREEZE SYSTEM TANKS**
- (Air operated)"
- 75 gallon polyethylene tank
- **WATER / ANTI-FREEZE REELS**
- 1/2" x 50' hose reel, includes hoses and ballstop
- **WATER / ANTI-FREEZE NOZZLES**
- Non-metered valve non drip (oil)

Contact Information

Craig Brown

Phone: 877-811-7665

Cell: 615-585-2729

Email: cbrown@bulldogcranes.com